

Doorbell Instruction Manual V3.0



Before using this product, read the Quick Guide carefully and save it for future referenceV3.0.

Indoor Monitor (Network Cable)

Indoor Monitor

1	9:41 () () () () () () () () () ()	- ②	 Screen Microphone Door 2/RX TX Door 1/RX TX Speaker Bell GND
3	9	- @ -	(7) GND TX RX VCC
		-	8 SD Card
4			9 Built-in Power Supply
5			1 Bracket Slot
6			(1) Unpolar input
	Unit Munice Control Co		12 Door 1 Lock/COM NC
			Door 2 Lock/COM NO
©		-	(4) 12V GND S4 S3 S2 S1

Call Panel (Network Cable) Outdoor Station



- (0 - (0 - (0) - (0) - (0)	
-11	

① Light Compensation
② HD Camera
③ Speaker
(4) IC/ID Card Reader
(5) Call Button
6) TX+TX-
(7) NC COM NO
(8) NC GND NO
Magnetic lock Power supply
(1) GND ADDR SW DET

1 Screw Hole

Outdoor Station Installation



Indoor Monitor Installation



Wiring Diagram(1 to 1) (Network Cable)



IP System - Villa 1 to 4 Diagram

Up to 4 pcs indoor monitor



IP System-Villa 2 to 4 Diagram



Features

1. IP 7" color capacitive full touch screen Tuya / Smart life app indoor monitor

2. View wide angle 110°, night vision, IP 65 waterproof outdoor station

 Video call, talk, intercom, room to room call, unlock
 Indoor monitor unlock, mobile Tuya remote control unlock, IC/ID/NFC cards unlock, connect with electric lock, keys to unlock

- 5.Support connect CCTV Camera by Onvif protocol
- 6. Monitoring & Snapshot photo or video when visitor calls
- 7. Photo and video records, support max 128G SD memory card
- 8. Support cascade between 4 indoor monitors and 2 call panels or add POE switch
- 9.Write resident name on the PVC board
- 10. Open 2 doors

7 Inch Full Touchscreen IP Indoor Monitor Interface Display



Add WIFI Tuya APP Connected with Mobile Phone Setting

Steps 1

The mobile phone should connect to the same WiFi as the monitor. Then download "Tuya Smart"or"Smart Life-Smart Living" from Google Play or APP Store. And register and login in your account.



Steps 2

Open the software and click"Add Device", and it will search and pair device.



Steps 3 When the WiFi monitor device is found, press "Add". And the device is being added.



Steps 4

In indoor monitor's WiFi setting, there is QR code after connecting WiFi Scan it and wait for adding.



Steps 5

Waiting for it's done, then press "Done". Finally, device is added successfully.



How to Share to Other Users

Steps 1

- 1. Log in to your account on the app on other family members' phones.
- 2. Another way is to add their accounts on your APP (Up to 20 members).

Found"Me"---enter the"Home Management".



Steps 2

You need to "Complete Home Information" if you don't use Tuya or Smart Life before. Just name this family group like "myhome". And in "Home Settings", add family members.

17:34:35 💄 🛛 🖓 🛱 🕅 🕅 🕻	94 09:20 0	न ∦ ि़ ‱।। 85।
Cancel Complete Home Information Sa	ave < Home Settings	
Home Name * Enter For example: myhom	Home Name	myhome >
Location Set	3 Room Management 6	> Room(s) >
Living Room	Location	To Be Set >
Master Bedroom	Manage Permissions	>
Second Bedroom	Home Member	
Kitchen	 Frank in SKYNEX wx-o9u_svvRRwu0f 	ne Owner >
Study Room	Add Member	
Add Room	Step 4.	
	Delete Home	

Steps 3

Input the account and name you want to share, and click Save to finish the sharing.

09:25	Remenber to Save	34)	09:24	От ∦ ि़, 56 III В4
Cancel	Add Member Sav	/e	< Home Sett	ings
Nam	e of member to be added			
Name	Juan		Home Name	myhome >
Region	China	>	Room Management	6 Room(s) >
Account	18450050175 Member registration		Location	To Be Set >
Only after acce owner become relevant functio	account(telephone or email) epting the invitation will the account a family member and be able to use ons.		Manage Permissions	>
Family Role	Common Member	>	Home Member	
			Frank in SKYNEX wx-o9u_svvRRwu0f	Home Owner >
			Waiting to join	Common Member >
			Add Member	
			Delete Ho	me

How to Add or Delete IC/ID Cards?

1. Find the "Advanced setting" and enter password "666666".



2.then "Card management".

	• Adv	vanced settin	g ••	6
Room Number	Device set	O IPC	Delete	Card Management
Change password	Format TF card	Reset		

3. Click the "+" to add cards.



4.Now, swipe cards in outdoor panel (Model: P9 series). After adding cards, click return. Test if the cards are valid or not.



5. If you need to delete cards, press bin icon.



6.In this delete cards interface, swipe the cards you want to delete in outdoor station. Then press return and the cards are removed.



7.Another method to delete cards is to click the card number you want to delete. Click "Delete" or "Delete all" in the options box according to your need.

8.After click "delete", the card is deleted.

	• Outdoor1	
No.	Card number	State
A Wester		

Specifications

Indoor Monitor

- •7 inch LCD 1024*600 pixel
- Internal power or POE
- •AC100-240V or DC 12-24V Power
- •ABS Plastic + PET
- •Support WIFI 2.4G
- ●Operating Temperature: -30°C~+60°C
- •Dimensions:230*145*26mm
- •Color: white+silver / black+grey optional
- Language: English/ Spanish / Russian/ Turkish / German / French/ Nederlands / Customize

Villa Outdoor Station

- •HD 1080P, 2MP Camera
- •DC 12-24V power from indoor monitor
- •Aluminum alloy +Acrylic panel material
- ●Operating Temperature:-40°C~+70°C
- •Color: white +silver
- •Dimensions: 122*48*20mm

Operations

Video Conference Call

To call the monitor, press the button on call panel. Then, the monitor. shows image of the call panel. Touch the button shown on the screen. to answer or hang up or unlock the door.

Monitor

- -To monitor call panel, touch the monitor button on the screen.
- -Touch call panel name to switch between call panels.
- -Touch photo or video button to record manually.
- -Touch sound button to adjust volume.
- -Touch unlock button to unlock the door.
- -Touch MIC button to mute.
- -Touch hang up button to finish monitoring.

Photo

- -When call panel calls the monitor, monitor will take a photo or video automatically according to settings.
- -While monitoring, touch the snapshot button to take a picture.
- -To check records, touch the records icon on the screen.

Setting

Ringtone	Set ringtones for indoor monitor
Record	Call records, photo or video according to settings
Date&Time	Set date and time
Turn Off Screen	Set screen off time
Delete	Delete all photos or videos
Language	Spanish / Russian/ Turkish / German / French/ Nederlands / Customize
Information	Check monitor information.
Reset	Restore factory settings

FAQ

NO	Malfunction	Reason	Solution	
1	Outdoor station can't call indoor monitor.	 Indoor monitor got reset Network cable quality or different standard. 	 1.In "Settings"-"Advanced setting "-"Room number", set room number as 04, extension number as "Master". password "6666666". 2.Use a 568B standard and good quality network cable. 	
2	Before installation ,it worked well. After installation, it can't call successfully.	1.Network cable quality. 2.Insufficient power supply voltage.	1.Use a good quality network cable. 2.Use a power adapter with output DC18V-24V,if the network cable is over 40 meters.	
3	When visitor was calling, only one of monitors is working.	1.Room number is the same.	1.For example, the room number of one monitor is "04"-"Master", and the another should be "04"-" Slave-1". If there are more screens then the room number should be " 01"-"slave-2" and "04"-"Slave-3".	
4	Why can't open the lock.	 Not use a power supply controller. Connect the wrong wire. 	 Use a power supply controller to power and control the lock. Please get and check the wiring diagram or video from technical support. 	
5	Why the indoor unit can't connect to the APP?	 Only the indoor unit with extension number "Master" can connect to the APP. The internet might not be good. 	 Set extension number as " Master". Then restart the indoor unit's WiFi. Try again when the network is stable. 	